

ZINDAGI BHAR NIBHAYE SAATH

Bada Dost Badhaye Dosti Ka Haath



INTRODUCING

**BADA
DOST i2**

TECHNICAL SPECIFICATIONS

BADA DOST i2 BS 6

Engine

Engine	1.5 L, 3 Cylinder Diesel Engine (BSVI)
Type	Diesel
Maximum Power @rpm	70 hp@3300 RPM
Maximum Torque @ rpm	190 Nm@1600-2400 RPM

Clutch

Clutch	240 mm Diaphragm, single dry plate ,mechanical cable operated
--------	---

Transmission

Type/No. of Gears	Fully synchromesh, 5 speed gearbox manual
Gear Shifting	Cable type

Brakes

Type	Vacuum assisted hydraulic brake with twin LCRV
------	--

Suspension

Front	Parabolic suspension with double acting shock absorber
Rear	Parabolic leaf suspension with double acting shock absorber

Tyres (Size/Type)

Tyres (Size/Type)	195 R15 LT
-------------------	------------

Weight

GVW (Gross Vehicle Weight) (kg)	2880
Rated Payload (kg)	1425 - FSD

Seating Capacity

Seating Capacity	Driver+2
------------------	----------

Fuel Tank Capacity

Fuel Tank Capacity (litre)	40 L
----------------------------	------

Dimensions

Overall Length (mm)	4818
Overall Height (mm)	2056
Wheelbase (mm)	2510
Load Body/Cargo Deck (LxBxH) (mm)	2745 x 1750 x 440 (9' x 5'9" x 1'5")

AUTHORISED DEALER

Arantya Auto

(A Unit of ARANTYA LOGISTICS PRIVATE LIMITED)

+91 8877480162 , 8877480160

For further details, please contact:

www.arantyaingroup.com

Or write to us at:

lcv@arantyaingroup.com

BIG ON COMFORT



BIG ON PERFORMANCE



BIG ON SAVINGS



BIG ON EXPERIENCE



*Terms & Conditions Apply.

*Disclaimer: Accessories shown are not part of the standard equipment. The illustrations are only indicative and may vary from the actual vehicle.

Ashok Leyland reserves the right to alter the technical specifications/designs without prior notice and without liability, in view of our policy of continuously improving our products.

Fuel efficiency is based on Ashok Leyland's internal test reports. 3 year or 1 lakh km whichever is earlier is provided by the manufacturer. August 2022.